

MINI XLR CHASSIS CONNECTOR

3 Pin Tiny XLR Female Panel Mount Connector

Locking 3 pin chassis connector with metal shell, gold plated pins, and solder cups for audio, lighting control, industrial automation, and test equipment. Designed for high RF environments.



IO-TXLR3-F-JLX

SPECIFICATIONS

PRODUCT

Gender: Female

Contacts: 3

ELECTRICAL

Contact Resistance: \leq 0.05 Ω

Insulation Resistance: $> 1 G\Omega$

Dielectric Strength: 1000V @ 60s

Current Rating: 5A / 50V AC

Ground Pin: Separate Ground Pin. Grounds Panel

and Mating Connector Shell

ENVIRONMENTAL

Standard Compliance: IEC 61076-2-103

UL Flammability: **UL94V-0**

Temperature Range: -40°C ~ +70° C (-40°F ~ +158°F)

MECHANICAL

Lifetime: > 1000 Mating Cycles

Wiresize: 0.50mm Max O.D.

Wiring: Solder Contacts

Locking Device: Latch Lock

Mounting Direction: Front

Solderability: Complies with IEC

60068-2-20

MATERIAL

Pins: Phosphor Bronze

Pin Plating: Gold

Grounding Terminal: Phosphor Bronze

Grounding Terminal Plating: Gold

Shell: Nickel Plated Zinc Alloy


Push Button: Nickel Plated Stainless

Steel

Latch: Stainless Steel



Panel Cutout



PART NUMBER BREAKDOWN:

IO-**TXLR**3-F-JLX Tiny XLR IO-TXLR3-F-JLX Number of Pins IO-TXLR3-F-JLX Gender IO-TXLR3-F-JLX Series Identifier

STANDARDS & CLASSIFICATIONS





