



AUDIO
TECHNOLOGIES®

MINI XLR CHASSIS CONNECTOR

3 Pin Tiny XLR Male Panel Mount Connector

Locking 3 pin chassis connector with metal shell, gold plated pins, and Vertical PCB Mount for audio, lighting control, industrial automation, and test equipment. Features a slotted nut and washer for lower profile installs.



IO-TXLR3-M-PV

SPECIFICATIONS

PRODUCT

Gender: **Male**

Contacts: **3**

ELECTRICAL

Contact Resistance: $\leq 0.05 \Omega$

Insulation Resistance: $> 1 \text{ G}\Omega$

Dielectric Strength: **1000V @ 60s**

Current Rating: **5A / 50V AC**

ENVIRONMENTAL

Standard Compliance: **IEC 61076-2-103**

UL Flammability: **UL94V-0**

Temperature Range: **-40°C ~ +70° C (-40°F ~ +158°F)**

MECHANICAL

Lifetime: **> 1000 Mating Cycles**

Wiresize: **0.50mm Max O.D.**

Wiring: **Vertical PCB**

Locking Device: **Latch Lock**

Mounting Direction: **Rear**

Solderability: **Complies with IEC 60068-2-20**

MATERIAL

Pins: **Brass**

Pin Plating: **Gold**

Shell: **Brass**

Shell Finish: **Nickel**

Latch: **Stainless Steel**

Nut: **Nickel Plated Brass**

Washer: **Nickel Plated Brass**


Insert: **PPS**

Product specifications may change without prior notification

Io Audio Technologies® is a registered trademark of Knight Electronics, Inc.
10557 Metric Dr. Dallas, TX 75243 | 214-340-0265 | 800-323-2439 | Fax: 214-340-5870 |
www.ioaudiotechnologies.com



Panel Cutout



PART NUMBER BREAKDOWN:

IO-TXLR3-F-PV

Tiny XLR

IO-TXLR3-F-PV

Number of Pins

IO-TXLR3-F-PV

Gender

IO-TXLR3-F-PV

Panel Mount

IO-TXLR3-F-PV

H = Horizontal PCB Mount

V = Vertical PCB Mount

STANDARDS & CLASSIFICATIONS



Product specifications may change without prior notification