

# FEATURES & BENEFITS

## SPECS

2  
(NO. OF CONDUCTORS)

26 AWG  
(CONDUCTOR SIZE)

CROSSLINKED  
POLYETHYLENE  
(INSULATION MATERIAL)

ALUMINUM &  
BRAIDED  
TINNED COPPER  
(SHIELD)

$\leq 14.4$  pF/ft  
(CAPACITANCE BETWEEN  
COND.)

$\leq 27.1$  pF/ft  
(CAPACITANCE BETWEEN  
COND. & SHIELD)

$0.152 \pm 1\%$   $\Omega$ /m  
(CONDUCTOR DC  
RESISTANCE)

## APPLICATIONS

BALANCED AUDIO

LOW VOLTAGE SIGNAL  
TRANSMISSION

CONTROL

HIGH NOISE  
ENVIRONMENTS



## BALANCED PATCH CABLE

### JACKET

Black, PVC jacket that protects the interior workings of the cable from the harsh environment and stage stress.

### CONDUCTOR

A single twisted pair of stranded 26 AWG conductors offers excellent signal transmission and also provides increased flexibility for years of continuous bending and use in live performances.

### DUAL SHIELD

An aluminum foil shield and a braided, tinned copper shield provide 100% coverage against EMI.

### INSULATION

XLPE insulation helps improve the dielectric strength of the cable and provides less shrinkage when soldering, while also insulating the conductors from current leakage.



### CONNECTOR OPTIONS PER SERIES



## CABLE ASSEMBLY AVAILABLE SIZES

3 ft	5 ft	10 ft	
15 ft	20 ft	25 ft	50 ft

## AVAILABLE BULK SPOOL SIZES

500 ft

(p/n IO-A12626-500SP)

Product specifications may change without prior notification

Io Audio Technologies® is a registered trademark of Knight Electronics, Inc.

10557 Metric Dr. Dallas, TX 75243 | 214-340-0265 | 800-323-2439 | Fax: 214-340-5870 | www.ioaudiotechnologies.com