

FEATURES & BENEFITS



PERFORMANCE SERIES XLR CABLE

SPECS

2
(NO. OF CONDUCTORS)

24 AWG
(CONDUCTOR SIZE)

POLYETHYLENE
(INSULATION MATERIAL)

SPIRALED
BARE COPPER
(SHIELD)

≤ 14.5 pF/ft
(CAPACITANCE BETWEEN
COND.)

≤ 24.9 pF/ft
(CAPACITANCE BETWEEN
COND. & SHIELD)

$0.075 \pm 5\%$ Ω /m
(CONDUCTOR DC
RESISTANCE)

APPLICATIONS

BALANCED AUDIO

LOW VOLTAGE SIGNAL
TRANSMISSION

CONTROL

JACKET

Black, PVC jacket that protects the interior workings of the cable from the harsh environment and stage stress.

SHIELD

Spiraled bare copper provides up to 95% coverage against EMI.

CONDUCTOR

A single twisted pair of stranded 24 AWG conductors offers excellent signal transmission and also provides increased flexibility for years of continuous bending and use in live performances.

RUBBER BOOT

Provides additional strain relief to withstand years of stress.

CONNECTORS

With silver plated contacts and a sturdy plastic insert that tightens onto the cable, these connectors will help provide a clean signal every time.



AVAILABLE SIZES

3 ft	6 ft	10 ft
25 ft	50 ft	100 ft

BULK WIRE AVAILABLE

This cable is available in 500ft spools (p/n IO-A12416-500SP)

Product specifications may change without prior notification

Io Audio Technologies® is a registered trademark of Knight Electronics, Inc.

10557 Metric Dr. Dallas, TX 75243 | 214-340-0265 | 800-323-2439 | Fax: 214-340-5870 | www.ioaudiotechnologies.com