

# FEATURES & BENEFITS



## U100 SERIES UNBALANCED CABLE

### SPECS

1  
(NO. OF CONDUCTORS)

20 AWG  
(CONDUCTOR SIZE)

CONDUCTIVE  
POLYETHYLENE  
(INSULATION MATERIAL)

SPIRAL  
BARE COPPER  
(SHIELD)

$\leq 33.3$  pF/ft  
(CAPACITANCE BETWEEN  
COND. & SHIELD)

$0.035 \pm 1\%$   $\Omega$ /m  
(CONDUCTOR DC  
RESISTANCE)

### APPLICATIONS

UNBALANCED AUDIO

LOW VOLTAGE SIGNAL  
TRANSMISSION

CONTROL

#### JACKET

Black, PVC jacket that protects the interior workings of the cable from the harsh environment and stage stress.

#### SHIELD

Spiral, bare copper provides up to 95% coverage against EMI.

#### INSULATION

Conductive PE insulation helps absorb changes in capacitance that occur when the cable is moved or stepped on.

#### CONDUCTOR

A single, stranded 20 AWG conductor offers excellent signal transmission and also provides increased flexibility for years of continuous bending and use in live performances.

### AVAILABLE SPOOL SIZES

100 ft

500 ft

Product specifications may change without prior notification

Io Audio Technologies® is a registered trademark of Knight Electronics, Inc.

10557 Metric Dr. Dallas, TX 75243 | 214-340-0265 | 800-323-2439 | Fax: 214-340-5870 | www.ioaudiotechnologies.com