

FEATURES & BENEFITS



3 PIN XLR CABLE CONNECTORS

SPECS

3
(NO. OF CONTACTS)

15 A @ 125 V AC
(VOLTAGE RATING)

SILVER OR GOLD
(CONTACT PLATING)

≤ 2.0 pF
(CAPACITANCE BETWEEN CONTACTS)

APPLICATIONS

BALANCED AUDIO

LOW VOLTAGE SIGNAL TRANSMISSION

INDUSTRIAL CONTROL

SILVER PINS

Silver plated pins extend the useful life and mating cycles. Available in silver and gold plated variations.

LATCH LOCK

Latch lock provides increased operational safety.



STRAIN RELIEF

Protects the cable from unintentional flexing to extend its useful life

ELECTROCOATED FINISH

Premium Electrocoated black finish protects the shell from dings and scratches.

SOLDER CUPS

These connectors feature solder cups for termination with bare wire ends of up to a max O.D. of 2.0mm (Male) 2.5mm (Female).

* Photo of IO-XLR3-M-BK & IO-XLR3-F-BK

Product specifications may change without prior notification

Io Audio Technologies® is a registered trademark of Knight Electronics, Inc.

10557 Metric Dr. Dallas, TX 75243 | 214-340-0265 | 800-323-2439 | Fax: 214-340-5870 | www.ioaudiotكنولوجies.com

FEATURES & BENEFITS



4 PIN XLR CABLE CONNECTORS

SPECS

4
(NO. OF CONTACTS)

10 A @ 125 V AC
(VOLTAGE RATING)

SILVER
(CONTACT PLATING)

≤ 2.0 pF
(CAPACITANCE BETWEEN CONTACTS)

APPLICATIONS

AUDIO

LOW VOLTAGE SIGNAL TRANSMISSION

LOW VOLTAGE DC POWER

CONTROL

COMMUNICATIONS

SILVER PINS

Silver plated pins extend the useful life and mating cycles.

LATCH LOCK

Latch lock provides increased operational safety.



STRAIN RELIEF

Protects the cable from unintentional flexing to extend its useful life

ELECTROCOATED FINISH

Premium Electrocoated black finish protects the shell from dings and scratches.

SOLDER CUPS

These connectors feature solder cups for termination with bare wire ends of up to a max O.D. of 2.0mm (Male) 2.5mm (Female).

* Photo of IO-XLR4-M-BK & IO-XLR4-F-BK

Product specifications may change without prior notification

Io Audio Technologies® is a registered trademark of Knight Electronics, Inc.

10557 Metric Dr. Dallas, TX 75243 | 214-340-0265 | 800-323-2439 | Fax: 214-340-5870 | www.ioaudiotechnologies.com

FEATURES & BENEFITS



5 PIN XLR CABLE CONNECTORS

SPECS

5
(NO. OF CONTACTS)

7.5 A @ 125 V AC
(VOLTAGE RATING)

SILVER OR GOLD
(CONTACT PLATING)

≤ 2.0 pF
(CAPACITANCE BETWEEN CONTACTS)

APPLICATIONS

STEREO BALANCED
AUDIO

LOW VOLTAGE SIGNAL
TRANSMISSION

CONTROL

SILVER PINS

Silver plated pins extend the useful life and mating cycles. Available in silver and gold plated variations.

LATCH LOCK

Latch lock provides increased operational safety.



STRAIN RELIEF

Protects the cable from unintentional flexing to extend its useful life

ELECTROCOATED FINISH

Premium Electrocoated black finish protects the shell from dings and scratches.

SOLDER CUPS

These connectors feature solder cups for termination with bare wire ends of up to a max O.D. of 1.25mm.

* Photo of IO-XLR5-M-BK & IO-XLR5-F-BK

Product specifications may change without prior notification

Io Audio Technologies® is a registered trademark of Knight Electronics, Inc.

10557 Metric Dr. Dallas, TX 75243 | 214-340-0265 | 800-323-2439 | Fax: 214-340-5870 | www.ioaudiotechnologies.com